

Be Off The Grid com Inc.
 1 Shawnee Church Road
 Shawnee on Delaware, PA 18356-0256
www.beoffthegrid.com
 1-908-507-5809



PHTO		Description
	Model	CZ-2500S
	DC Voltage	12V or 24V or 48V or 110V
	Voltage Range	10-15VDC or 21-30VDC or 42-60VDC or 100-120VDC
	No Load Current Draw	<0.5
	Efficiency	> 85%
	DC Connector	Cables With Clips or Car Adaptor
	AC Voltage	100/110/120VAC or 220/230/240 VAC
	Continuous Power	2500W
	Surge Power	5000W
	Waveform	Sine wave
	Frequency	50Hz or 60Hz
	AC Regulation	3%
	Low Voltage Alarm	10DC±0.5V or 20.5DC±1V or 44VDC±1V or 100VDC±1V
	Low Voltage Shut Down	9.5DC±0.5V or 19.5DC±1V or 42VDC±1V or 96VDC±5V
	Over Load	Output shut off
	Over Voltage Shut Down	15.5V or 30.5V or 61.2V or 120V
	Over Thermal	Output automatic shut off
	Fuses	Fuse
	Working Temperature	-10°C to +50°C
	Working Humidity	20%~90%RH
	Storage Temperature	-30°Cto +70°C
	Machine Size(mm)	366X151X155
	Packing Size(mm)	480X210X205
	Net Weight(kg)	4.83
	Gross Weight(kg)	5.57
	Packing Mode	Cardboard box
	Start	Soft start
	Cooling Ways	Fan cooling
	Total Harmonic Distortion	THD < 5%

Visit our website www.beoffthegrid.com for additional products and services